


Kongres Container

Application requirements for communication base station power supply



Overview

Power solutions for wireless networks applications must have a wide voltage range, high power density, compact size, excellent reliability, high efficiency, and low no-load power consumption. Can a 500W switch power supply be used for communication base stations?

Conferences > 2023 4th International Confer. In order to meet the high power and high stability requirements of communication base stations for power supply, this paper designs a dedicated 500W switch power supply for communication base stations.

What is a preferred power supply architecture for DSL applications?

A preferred power supply architecture for DSL applications is illustrated in Fig. 2. A push-pull converter is used to convert the 48V input voltage to +/-12V and to provide electrical isolation. Synchronous buck converters powered off of the +12V rail generate various low-voltage outputs.

What is a 3G base station converter?

In a 3G Base Station application, two converters are used to provide the +27V distribution bus voltage during normal conditions and power outages.

Which power supply is best for a BBU & RRU?

A power supply with a capacity of 100 W to 350 W was sufficient to cover many applications. Forward converters were a good choice and have been employed for years in telecom BBUs and RRUs. With the growing demand for mobile data, new markets and applications continue to emerge.

What is a multi-output power supply design?

Multiple output designs may also employ a complex regulation scheme which senses multiple outputs to control the feedback loop. Voice-over-Internet-Protocol (VoIP), Digital Subscriber Line (DSL), and Third-generation (3G) base stations all necessitate varying degrees of complexity in power supply design.

What types of power systems are used in communications infrastructure equipment?

Communications infrastructure equipment employs a variety of power system components. Power factor corrected (PFC) AC/DC power supplies with load sharing and redundancy (N+1) at the front-end feed dense, high efficiency DC/DC modules and point-of-load converters on the back-end.

Application requirements for communication base station power su

Contact Us

For catalog requests, pricing, or partnerships, please visit:
<https://www.drugiswiatowykongrespolakow.pl>