

Kongres Container

Pvb double glass solar module building curtain wall

12.8V6Ah



Nominal voltage (V):12.8
Nominal capacity (ah):6
Rated energy (WH):76.8
Maximum charging voltage (V):14.6
Maximum charging current (a):6
Floating charge voltage (V):13.6~13.8
Maximum continuous discharge current (a):10
Maximum peak discharge current @10 seconds (a):20
Maximum load power (W):100
Discharge cut-off voltage (V):10.8
Charging temperature (°C):0~+50
Discharge temperature (°C): -20~+60
Working humidity: <95% R.H (non condensing)
Number of cycles (25 °C, 0.5c, 100%dod): >2000
Cell combination mode: 32700-4s1p
Terminal specification: T2 (6.3mm)
Protection grade: IP65
Overall dimension (mm):90*70*107mm
Reference weight (kg):0.7
Certification: un38.3/msds

Overview

How does a double-glazing PV curtain wall work?

In the hybrid system, the ventilated double-glazing PV curtain wall provided reheat energy for the subcooled supply air while effectively cooling the PV façade. It efficiently facilitated solar-electric conversion and excess heat recovery (HR), thereby enhancing the electrical and thermal performance of the building.

What is a VPV curtain wall?

The VPV curtain wall consists of a piece of CdTe-based PV laminate glass, an air cavity, and a sheet of vacuum glazing. The solar cells are etched into strips by lasers, and the transmittance of the VPV sample can be adjusted by changing the arrangement density of the strip solar cells.

How does a photovoltaic curtain wall work?

A photovoltaic curtain wall coupled with an air-conditioning system is designed. Curtain wall cooling and supply air reheating are achieved using heat recovery. System performance is evaluated, taking an office in hot-humid summer as a case. The system increases power output by 1.07% and achieves 27.51% energy savings.

What is building integrated photovoltaic (BIPV) technology?

As an effective method of solar energy utilization, building integrated photovoltaic (BIPV) technology occupies a prominent position in building enhancement. The photovoltaic (PV) modules not only serve as building façade materials but also generate electricity.

Can a PV double-glazing ventilated curtain wall reduce cold-heat offset?

Properly increasing channel thickness and photovoltaic coverage optimizes design. To address the problems of PV facade overheating and air-conditioning cold-heat offset, this study proposed a novel PV double-glazing

ventilated curtain wall system (PV-DVF) that combined PV cooling and dew-point air reheating.

Are VPV curtain walls mutually constraining?

However, there is a lack of in-depth, performance-driven optimal design that considers the mutually constraining functions of the VPV curtain wall. To address this issue, this study proposed a multi-function partitioned design method for VPV curtain walls aimed at reconciling the competing demand of different functions.

Pvb double glass solar module building curtain wall

Contact Us

For catalog requests, pricing, or partnerships, please visit:
<https://www.drugiswiatowykongrespolakow.pl>